

# NEWJET™ – Ref. 804

## THE GLOSSY PRINTABLE MEDIA DEDICATED TO PERSONALISATION OF LIGHT COLOURED TEXTILES

Looking to personalise textile supports with a homedesk inkjet printer? Newjet is a printable media with a glossy finish and soft touch fully compatible with homedesk printers and it is dedicated for light coloured textile.

### Fashion Accessories



### Product description

- ✓ Specially developed for home desk printers (inkjet printers).
- ✓ Fast drying inks process → saves production time.
- ✓ Good opacity.
- ✓ Glossy finish with an extra transparent effect.
- ✓ Soft-touch.
- ✓ Very comfortable to wear, thanks its thinness.

### Application key points

- ✓ No tape needed for application → saves money.
- ✓ The designs are directly printed on the product.
- ✓ Also compatible with solvent and eco-solvent inks.
- ✓ Easy to cut thanks its thinness.
- ✓ Specially for medium designs and logos.

### Usage benefits

- ✓ Specially suitable for light coloured textiles.
- ✓ Recommended for home deco and fashion accessories.

## SPECIFICATIONS

Average Thickness	Composition	Dimensions	Inks compatibility
85µm	Clear satiny film	<b>Available in:</b> A3 A4 144cm x 20m 72cm x 20m	Desktop inkjet Check our website for technical Advice

## APPLICATION INSTRUCTIONS

Applies on	Application Temp. & Duration
Light coloured textiles such as Cotton Polyester Acrylic and similar fibers	160°C – 20 s 320°F – 20 s

Pressure	Peeling	Recommended Transfer
Medium	Cold	By Hand

### Step 1 – Print & Cut

Program the printing and cutting of the design without rotating the images. Define the cut marks, we recommend to cut the product by hand.

### Step 2 – Weeding

Remove the excess material (easy weeding).

### Step 3 – Application

Pre-press the textile for about 5 seconds to flatten it and release any excess moisture.

Position your design on the textile and press it with a Sefa DUPLEX/ROTEX or equivalent at 160°C/320°F for 20 seconds with a medium pressure.

We do recommend the use of a silicone paper to protect the designs and the textile during application.

### Step 4 – Peeling

Peel when cold.

*NOTE: We highly recommend you to perform tests before launching a production.*

## CARE AND MAINTENANCE RECOMMENDATIONS

Washing	Ironing	Tumble-dry	Dry cleaning
Up to 40°C/104°F	On reverse side only	Yes	Not recommended

Storage life	Storage Temperature	Storage Lighting	Position
Up to 1 year	Dry room with 15°C-30°C/ 59°F-86°F	Away from sunlight	Vertical position

### Care and maintenance:

- ✓ Respect the garments' instructions.
- ✓ Follow the instructions provided by the printer manufacturer.
- ✓ It is important to always use official inks from the printer manufacturer.
- ✓ Printable media are very sensitive: always handle with care and preferably with gloves.
- ✓ Wait 24 hours before the first wash.
- ✓ Avoid the use of aggressive products.

### Washing recommendations:

- ✓ Preferably inside out to extend design life.
- ✓ Do not bleach.