

ATT 500™ — Ref. 5500

THE MEDIUM TACK AND NO BACKING TAPE

Looking for a medium tack application tape without backing? This application tape ATT 500 is unrolled on itself (no backing) which is perfect to reduce time and material waste.



Product description

- ✓ Medium tack → doesn't damage the product during the transfer.
- ✓ No backing, quick application → saves production time.
- ✓ Perfect for massive productions, manually or using laminator.

PRODUCT APPLICATION

| PRODUCTS | ATT 490 | ATT 500 Medium tack No backing | ATT 450 | ATT 600 |
|-------------------------|---------|--------------------------------------|---------|---------|
| POLYURETHANE | | | | |
| HOTMARKPRINT REVOLUTION | | | ✓ | |
| HOTMARKPRINT | ✓ | ✓ | ✓ | |
| HOTMARKPRINT SIR | ✓ | ✓ | ✓ | |
| HOTMARKPRINT NYLON | ✓ | ✓ | ✓ | |
| FIFTYPRINT | ✓ | | ✓ | |
| SPECIAL EFFECTS | | | | |
| GLITTERPRINT | | | | ✓ |
| METALPRINT | | ✓ | | |
| VINYL | | | | |
| EASYPRINT | ✓ | ✓ | ✓ | |
| EASYPRINT SIR | ✓ | ✓ | ✓ | |
| EASYPRINT NYLON | ✓ | ✓ | ✓ | |
| APRINT | | | ✓ | |
| SUNMARKPRINT | | | ✓ | |
| FLOCK | | | | |
| FLOKPRINT | | | ✓ | |

SPECIFICATIONS

| Tack | Average Thickness | Dimension | Storage temperature |
|--------------|-------------------|------------|--------------------------------------|
| Medium ++ | 110 µm | 50cm x 25m | Dry room with 15°C-30°C/59°F-86°F |

